

COFFEE AND TEA ARE 98% WATER

Everpure® filters by Pentair® reduce:

- Abrasion and clogging
- Scale buildup and corrosion
- Off-tastes and odors
- Harmful cysts by mechanical means*

The benefits of Everpure filtration:

- Consistent quality, better tasting coffee
- Less equipment downtime and lower energy costs
- Lower maintenance and equipment costs, and lower total cost of ownership
- Satisfied customers and increased profits

NEW

**CONSERV 75E
HIGH EFFICIENCY
RO SYSTEM NOW
AVAILABLE!**

SEE PAGE 41 FOR MORE INFORMATION.

EVERPURE COFFEE FILTRATION SYSTEMS

- NSF certifications
- 1/2 micron precoat filtration by mechanical means* with scale control
- Chlorine, taste & odor and sediment reduction
- Harmful cyst reduction by mechanical means*
- Proprietary Micro-Pure® II filtration media effectively inhibits the growth of bacteria on the filter media that can decrease product life*

System sizing guidelines: Our system sizing guidelines are approximations based on properly installed equipment, average usage at normal operating flow rate and average water conditions. These guidelines are designed to give you approximately six (6) months of use between filter cartridge changes. Variations in equipment usage and/or incoming water conditions may produce different results.

SYSTEM	EQUIPMENT TYPE	EQUIPMENT FLOW RATE DEMAND		RATED CAPACITY**		OVER 6 MONTH PERIOD	
		GPM	LPM	GALLONS	LITRES	GALLONS	LITRES
QL2-OCS ²	Brewers 0.50 gpm and under	0.50	1.89	1,500	5,677	3,000 1/2 Gal Pots	11,000 2 L Pots
QL3-BH ²	Brewers 0.50 gpm - 1.0 gpm	0.50	1.89	3,000	11,355	6,000 1/2 Gal Pots	23,000 2 L Pots
QC7I-MH ²	Brewers 1 gpm - 1.67 gpm	1.00	3.79	9,000	34,065	18,000 1/2 Gal Pots	68,000 2 L Pots
QC7I Twin-MH ²	Brewers 1.67 gpm and above	1.00	3.79	18,000	68,100	—	—

UP TO 0.50 GPM

QL2-OCS², QL3-BH² and 2FC-S



QL2-OCS²

QL3-BH²

2FC-S

UP TO 1.67 GPM

QC7I Single-MH²



QC7I Single-MH²

Note: Filter head and cartridge sold separately.

SYSTEM	PART NO	MICRON RATING	FLOW RATE		RATED CAPACITY		DIMENSIONS (H X W X D)		SHIP WT		LIST PRICE	NSF
			GPM	LPM	GALLONS	LITRES	IN	CM	LBS	KGS		
QL2-OCS ²	EV9275-60	0.5	0.50	1.89	1,500	5,678	12 x 3.75 x 4	30.50 x 9.70 x 10.20	3.0	1.4	\$132.00	42, 53
QL3-BH ²	EV9272-00	0.5	0.50	1.89	3,000	11,356	16.50 x 3.75 x 4	42 x 9.70 x 10.20	4.0	1.8	193.00	42, 53
2FC-S	EV9691-76	0.5	1.50	5.68	6,000	22,712	10.25 x 3.25	26.04 x 8.26	6.6	3.0	86.30	42, 53
QC7I Single-MH ²	Head: EV9272-41 Cartridge: EV9613-21	0.5	1.67	6.32	9,000	34,069	27.50 x 5.60 x 4	70 x 14.20 x 10.20	6.0	2.7	288.00 153.00	42, 53

*See individual system specification sheets for performance claims and FIFRA registration information.

**System capacity may be reduced in areas where higher levels of particulates exist in the water, decreasing the flow rate through the filter system over time. Replace cartridge if flow rate is reduced below the rate demanded by the equipment.