



S700



Inspire coffee creativity. Do, you want to create memorable and individualized experiences for your customers while providing the highest caliber of in-cup-quality? The S700 is the answer! This espresso machine merges the convenience and consistency of a fully automatic machine with the craft and creativity of a two-step machine. With patented iQFlow™ technology that delivers superior – and consistent – coffee extraction, customizable milk profiles with independent control of aeration and temperature, and a three-boiler system designed to meet all your milk-steaming requirements, the S700 is here to help baristas unleash their full creative potential. So, if you're looking for the best mix of human creativity, coffee competence, craft, and advanced coffee making technology, turn to the S700.

Innovation becomes an invitation.

UNIT	CUPS PER DAY
S700	Up to 250



iQFlow™

Groundbreaking technology that extracts more flavor for unrivaled in-cup-quality.



Advanced Steam Spout

Engineered for professionals with Autosteam or Autosteam Pro.



Franke Digital Services

A clear view of commercial and operational performance.


Technical Data

Machine Models


Model	Specification	
S700		
Electrical Connection	208V (30A)	
Dimensions	13.4"W x 33.5"H in x 21.3"D	
Weight (empty)	Approx. 135 lbs	



Standard Configuration
Front Profile and Clearances



Side Profile



Water quality requirements

Aroma	Fresh and pure taste, with no perceptible aroma
Color	Clear
Total Hardness	70 – 140 ppm (mg/l)
Carbonate hardness	3 – 6° dH CH (carbonate hardness)
	50 – 105 ppm (mg/l)
Acid content/ph value	6.5 – 7.5 pH
Chlorine content	< 0.5 mg/l
Chloride content	< 30 mg/l
TDS (Total dissolved solids)	30 – 150 ppm (mg/l)
Electrical conductivity	50 – 200 µS/cm (microsiemens)
Iron Content	< 0.3 mg/l
Water pressure	80 – 800 kPa (0.8 – 8 bar)
Flow rate	> 0.1 l/sec
Water temperature	< 25°C

Water connection and drain


Water connection	3/8" compression fitting, L = 59"
Drain hose	Dia = 0.75" OD, L = 78.7"

Digital services connectivity requirements

OPTION 1		
Ethernet/LAN Recommended Option	Connectivity Requirements Ethernet/LAN	
	MQTT	Port 8883
	NTP	Port 123
	HTTPS	Port 443
	MQTT Websockets	Port 443/ Port 444
OPTION 2 Additional costs may apply		OPTION 3 Limitations may apply
Franke Connection KIT Cellular/ WiFi (Modem)		3rd Party Cellular Modem/ WiFi
Mobile: Private APN (Roaming partner) 4G		Mobile: Cellular or WiFi connection
2 x LAN ports to connect		Customer provides modem
Modem connects up to 2 machines		
Wifi capability upon request		

Customer is responsible for all connectivity.

Utility and Grounds Chute Openings



ETL LISTED CONFORMS TO
UL STD 197 CERTIFIED TO
CSA STD C22.2
NO 10931 | 123505



CONFORMS TO
NSF STD 4